

TECHNICAL SPECIFICATIONS :

General Information

Generic Name	Area Star
Product Code	PLFL 512 / 200 / xx
Product Ordering Code	PLFL 512 / 80 / 700
Light Source	SMD Type High Power LED
Driver	Yes – Constant Current
Surge Protection Device	Yes – 10kV

Performance

Luminaire Output	Up to 25100 lm
------------------	----------------

Optoelectronics

Color rendering index (CRI)	>70
Correlated Color Temperature	6500K / 5000K / 2700K
Beam angle of light source	120°

Operating & Electrical

Voltage Input	130 to 280 VAC
Current Input	< 920mA @ 230 VAC
Power Input	≤ 200Watt

Luminair Body

Hosing Material	Anodized Extruded Aluminium (Copper Content <0.1%)
Hosing Finished	Powder Coated

Electronics

Driver	Single Stage Fly back with PF Correction C.C. Driver
Setup rise holdup time for driver	< 0.5 sec

Protection

Surge Protection	6.5 kV - Inbuilt in Driver
Voltage Protection	Phase to Phase protection of 440V. for 8 hrs.
Ingress protection code	IP - 66



Power Absorption	Up to 200Watt
------------------	---------------

Luminous Efficacy	165 Lumens / Watt
Optic type	Optional - High efficiency Polycarbonate Lens of 60° / 30°
Median useful life L70B50	50,000 Hour(s)

Line Frequency	50 Hz
Power Factor	≥ 0.95
Working Temperature	- 10° C - +50° C.

Optical Cover Material	Heat Resist 4mm Thick Toughened glass
Mounting Bracket	Adjustable cradle, 3 circular slots of 10mm Ø at center distance of 60mm.

Efficiency of Driver	≥ 87%
THD in %	≤ 10% (Full Load)

Over Heat Protection	Yes (Drop Output Current)
Short Circuit Protection	Yes (Auto recovery)
impact protection code	IK - 05