

TECHNICAL SPECIFICATIONS :

General Information

Generic Name	FLP Street Light
Product Code	PLFS 538 / 30 / xx
Product Ordering Code	PLFS 538 / 42 / 100
Light Source	SMD Type High Power LED
Driver	Yes – Constant Current
Surge Protection Device	Yes – 10kV



Performance

Luminaire Output	Up to 3800 lm
------------------	---------------

Power Absorption	Up to 30Watt
------------------	--------------

Optoelectronics

Color rendering index (CRI)	>70
Correlated Color Temperature	6500K / 5000K / 2700K
Beam angle of light source	120°

Luminous Efficacy	150 Lumens / Watt
Optic type	N.A
Median useful life L70B50	50,000 Hour(s)

Operating & Electrical

Voltage Input	130 to 280 VAC
Current Input	< 135mA @ 230 VAC
Power Input	≤ 30Watt

Line Frequency	50 Hz
Power Factor	≥ 0.95
Working Temperature	– 10° C - +50° C.

Luminair Body

Hosing Material	LM-6 Grade Aluminium Alloy
Hosing Finished	Epoxy Powder Coated - Dark Grey 632 as per IS-5

Optical Cover Material	Heat Resist 8mm Thick Toughened glass
Mounting Bracket	Pole Mounting with Bracket Arm of 52mm Max.

Electronics

Driver	Single Stage Fly back with PF Correction C.C. Driver
Setup rise holdup time for driver	< 0.5 sec

Efficiency of Driver	≥ 87%
THD in %	≤ 10% (Full Load)

Protection

Surge Protection	6.5 kV - Inbuilt in Driver
Voltage Protection	Phase to Phase protection of 440V. for 8 hrs.
Ingress protection code	IP - 65

Over Heat Protection	Yes (Drop Output Current)
Short Circuit Protection	Yes (Auto recovery)
impact protection code	IK - 05

Certification under the Brand logo GFEC Model No.: GFEC-CL-01

CIMFR Certificate No.	IN/CIMFR/TR22/P/H385
-----------------------	----------------------

PESO Certificate No.	P-576488/1
----------------------	------------