

TECHNICAL SPECIFICATIONS :

General Information

| | |
|--------------------------------|-------------------------|
| Generic Name | FLP Well Glass |
| Product Code | PLFW 539 / 35 / xx |
| Product Ordering Code | PLFW 539 / 48 / 100 |
| Light Source | SMD Type High Power LED |
| Driver | Yes – Constant Current |
| Surge Protection Device | Yes – 10kV |



Performance

| | |
|------------------|---------------|
| Luminaire Output | Up to 4300 lm |
|------------------|---------------|

| | |
|------------------|--------------|
| Power Absorption | Up to 35Watt |
|------------------|--------------|

Optoelectronics

| | |
|------------------------------|-----------------------|
| Color rendering index (CRI) | >70 |
| Correlated Color Temperature | 6500K / 5000K / 2700K |
| Beam angle of light source | 120° |

| | |
|---------------------------|-------------------|
| Luminous Efficacy | 150 Lumens / Watt |
| Optic type | N.A |
| Median useful life L70B50 | 40,000 Hour(s) |

Operating & Electrical

| | |
|---------------|-------------------|
| Voltage Input | 130 to 280 VAC |
| Current Input | < 160mA @ 230 VAC |
| Power Input | ≤ 35Watt |

| | |
|---------------------|-------------------|
| Line Frequency | 50 Hz |
| Power Factor | ≥ 0.95 |
| Working Temperature | – 10° C - +50° C. |

Luminair Body

| | |
|-----------------|--|
| Hosing Material | LM-6 Grade Aluminium Alloy |
| Hosing Finished | Epoxy Powder Coated - Dark Grey 632 as per IS-5 |

| | |
|------------------------|---------------------------------|
| Optical Cover Material | Heat Resist tempered dome glass |
| Mounting Bracket | Electroplated Eye bolt . |

Electronics

| | |
|-----------------------------------|---|
| Driver | Single Stage Fly back with PF Correction C.C. Driver |
| Setup rise holdup time for driver | < 0.5 sec |

| | |
|----------------------|-------------------|
| Efficiency of Driver | ≥ 87% |
| THD in % | ≤ 10% (Full Load) |

Protection

| | |
|-------------------------|---|
| Surge Protection | 6.5 kV - Inbuilt in Driver |
| Voltage Protection | Phase to Phase protection of 440V. for 8 hrs. |
| Ingress protection code | IP - 66 |

| | |
|--------------------------|---------------------------|
| Over Heat Protection | Yes (Drop Output Current) |
| Short Circuit Protection | Yes (Auto recovery) |
| impact protection code | IK - 05 |

Certification under the Brand logo GFEC Model No.: GFEC-WG-60

| | |
|-----------------------|---------------------|
| CIMFR Certificate No. | IN/CIMFR/TR21/P/H17 |
|-----------------------|---------------------|

| | |
|----------------------|---------|
| PESO Certificate No. | Applied |
|----------------------|---------|